Price Schedule for Goods Offered from Within the Philippines [shall be submitted with the Bid if bidder is offering goods from within the Philippines]

For Goods Offered from Within the Philippines

Name of Bidder	Project ID No	Pageof

1	2	3	4	5	6	7	8	9	10
ltem	Description	Country of origin	Quan tity	Unit price EXW per item	Transportati on and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+8)	Total Price delivered Final Destination (col 9) x (col 4)
	LOT 1: LOCAL SERVER SYSTEM FOR LOCAL CLOUD (STORAGE)								
1	 Technical Specifications: 1 x Storage Node (Must be compatible with existing custom Dell T640 server to ensure and maximize compatibility): Integrated remote server management software must be iDRAC9, Enterprise 15G (Group Manager Enabled) OS must be open source (preferably Ubuntu Server) At least 512GB RAM 3200MT/s RDIMMs At least 15TB SSD (Transfer buffer cache), 12Gbps 100TB HDD Usable Capacity (200TB HDD Raw Capacity RAID 10 Configuration) Enterprise grade at least 7,200RPM, 12Gbps 2 CPU Configuration Intel Xeon processor, each CPU with the following: at least Silver 		1						

r		
		o at least 2.3 GHz
		o at least 20 Cores, 40 Threads
		o at least 24M Cache, DDR4-2666
	0	1 x Broadcom 57508 Dual Port 100GbE QSFP Adapter,
		PCIe Low Profile
	0	1 x Broadcom 57416 Dual Port 10GbE BASE-T Adapter,
		OCP NIC 3.0
	0	2 x QSFP28 SR4 100GbE 85C optic transceivers
	0	Rack rails with cable management arm
	0	With installation, configuration, and knowledge transfer
•	1 x	Smart-UPS SRT 3000VA 230V 2700 Watts
	0	lead-acid battery type
	0	double conversion online
	0	runtime full load: at least 3 minutes 58 seconds
	0	battery lifespan: at least 3 years
	0	wave type: sine wave
	0	bypass type: internal bypass (automatic and manual)
	0	USB compatible
	0	must be compatible with PowerChute UPS management
		software
	0	rack-mounted with kit
	0	with multifunction LCD status and control console
	0	with audible and visible alarms
	0	heat dissipation: 703 Btu/h
	0	protection: IP20
1	0	power socket outlets:
		• 8 IEC 60320 C13
		• 2 IEC Jumpers
		• 2 IEC 60320 C19
	0	input connection type:
		BS1363A British
		• IEC 60320 C20
		Schuko CEE 7 / EU1-16P
1	0	3 years repair or replacement and 2 years for battery
	0	with installation, configuration, and knowledge transfer
Inc	lusior	15:
	• 3 ye	ars warranty, onsite services, and ProSupport

 Inclusive of installation, service and delivery fees, and all other charges 				

Name:	
.egal Capacity:	
Signature:	

Duly authorized to sign the Bid for and behalf of: _____