## (TECHNICAL SPECIFICATIONS)

**BID NO: PBM 2024-**09

DATE:

REQUIRED SPECIFICATIONS	OFFERED SPECIFICATIONS (please write down detailed offered specifications)	REFERENCES (include supporting documents) (attached brochure / technical data/ website, etc.)
LOT 1: SUPPLY AND INSTALLATION OF CCTV PROJECT FOR UP MINE	DANAO	
1. HYBRID NETWORK VIDEO RECORDER		
At least 4K HDMI Video Output & 16MP Decoding Capacity: At least 8-ports PoE+, PoE Budget: 113 W At least 8-Channel Simultaneous Playback. Replay the feed from up to 8 cameras simultaneously, increase replay speed, and find events in the recorded video.		
At least H.265+ At least Two-Way Audio support At least ONVIF Compatibility		
At least support 24/7 Continuous Recording. At least support up to 10 TB storage. At least support Remote Monitoring: Should have a dedicated app, web UI, and Security Manager/VMS which enable remote monitoring, providing ease and convenience. At least 1 HDMI and 1 VGA Interface: Supports independent video output. At least Plu	g g	
& Play: Allows new and unused IP Cameras to be added automaticall to the new NVR and activated instantly, making installation faster. The Video Management Software Clients should support Microsoft Windows, MAC, IOS, and Android for remote management It should support the existing Bosch DIVAR IP all-in-one 7000 3U		
bundled with Video Management Software and should support Network Attached Storage (NAS). It should be the same brand as the new CCT cameras to be supplied.  At least Remote Monitoring. At least 80 Mbps of incoming bandwidth	TV	
At least 60 Mbps outgoing bandwidth. At least HDMI and VGA Vide Outputs. At least a 3-year Warranty.		
Note to Bidders: The terms of payment shall be as follows: <i>upon</i> complete delivery of all items/services.	Name of Representative Position	
	Address _ Telephone/Fax/Email _	

## 2. HYBRID NETWORK VIDEO RECORDER At least 4K HDMI Video Output & 16MP Decoding Capacity: At least 16-ports PoE+, PoE Budget: 140 W. At least 16-Channel Simultaneous Playback. Replay the feed from up to 8 cameras simultaneously, increase replay speed, and find events in the video schedule. At least H.265+ At least Two-Way Audio support At least ONVIF Compatibility At least support 24/7 Continuous Recording At least support up to 24 TB storage At least support Remote Monitoring: Should have a dedicated app, web UI, and Security Manager/VMS which enable remote monitoring, providing ease and convenience. At least 1 HDMI and 1 VGA Interface: Supports independent video output. At least include Perpetual license. Scope of Work Supply, Installation, and Configuration for the Network Recorder/s/Network Video Recorder/s Supply, Installation, and Configuration of the Video Management Software for the NVR Supply, Installation, and Configuration of the Video Management Software Clients for the workstations (at least 5 clients) The Video Management Software Clients should support Microsoft Windows, MAC, IOS, and Android for remote management Should support the existing Bosch DIVAR IP all-in-one 7000 3U bundled with Video Management Software and should support Network Attached Storage (NAS) Integrate existing 8 IP Cameras in CARIM 2 to the Hybrid Network Video Recorder Should be the same brand with the new CCTV cameras to be supplied. At least Remote Monitoring At least 80 Mbps incoming bandwidth At least 60 Mbps outgoing bandwidth At least HDMI and VGA Video Outputs At least 3-year Warranty Note to Bidders:

Signature of Representative	
Name of Representative	
Position	
Company	
Address	
Telephone/Fax/Email	
• • • • • • • • • • • • • • • • • • • •	

3. <b>6TB</b> 256MB Cache 3.5-inch SATA 6Gb/s Internal H NVR	IDD for
4. 10TB 256MB Cache 3.5-inch SATA 6Gb/s Interna	al HDD
5. 2MP Outdoor Full-Color Bullet Network Camera SPEC H.265+/H.265/H.264+/H.264, 1/3" Progressive Scan Cl Color/0.005 Lux@F1.6, 0 Lux with IR/White Light, 25fps/30: (2560x1440,2304x1296, 2048x1280,1920x1080), PoE/12V D 2.8/4/6mm Fixed Lens, Built-In Microphone, Speaker, micro- Slot, IP66 FEATURE: Full-Color and IR Night Vision (Up to 30 m), Defense, Two-Way Audio, On-Board Storage, Smart Dete (Human &Vehicle Classification) (Motion Detection, Area Intrusion Detection, Line-Crossing Detection, Camera Tan Detection, Abandoned Object Detection, Object Removal Detection, Area Entrance Detection	fps C, SD Active ction
6. 4MP Full-Color DOME(TURRET) Network Camer SPEC: H.265+/H.265/H.264+/H.264, 1/3" Progressive Scat Color/0.005 Lux@F1.6, 0 Lux with IR/White Light, 25 (2560x1440,2304x1296, 2048x1280, 1920x1080), PoE/12V mm Fixed Lens, Built-In Microphone, micro-SD Slot, IK10, IF FEATURE: Full-color and IR Night Vision (Up to 30 in Detection (Human & Vehicle Classification) (Motion Detection Detection, Line-Crossing Detection, Camera To Detection, Abandoned Object Detection, Object Removal Area Entrance Detection, Area Exiting Detection	n CMOS, 5fps/30fps DC, 2.8/4 P67. m), Smart tion, Area Campering
7. 4MP Pan/Tilt Network Camera SPEC: H.265+/H.265/H.264+/H.264, 1/1.8" Progressive Scan Color/0.0005 Lux@F1.0, 0 Lux with White Light, 25fp (2688x1520,2304x1296, 2048x1280, 1920x1080), PoE/12V mm Fixed Lens, Built-In Microphone, Speaker, micro-SD Slo FEATURE: Color Pro Night Vision (Up to 30 m), AI Pro (Fac People & Vehicle Analytics), Customized Patrol, Automatic Active Defense, Two-Way Audio, On-Board Storage, Smart I (Human &Vehicle Classification) (Motion Detection, Area Detection, Line-Crossing Detection, Camera Tampering Abandoned Object Detection, Object Removal Detection Entrance Detection	s/30fps DC, 4 t, IP66 e Capture, Tracking, Detection Intrusion Detection,
Note to Bidders: The terms of payment shall be as follows: upon complete delivery of all items/services.	Signature of Representative  Name of Representative  Position  Company  Address  Telephone/Fax/Fmail

8. Gigabit Single Mode Fiber to Ethernet Media Converter A for long-distance camera At least Dual SC Fiber, 1000Base-LX to 10/100/1000Base-Tx Gigabit SMF Fiber SC to Copper RJ45 Ethernet Converter, UL Certified, up to 2km, 1550 nm TX, 1310 nm RX		
9. Gigabit Single Mode Fiber to Ethernet Media Converter B for long distance Cameras At least Dual SC Fiber, 1000Base-LX to 10/100/1000Base-Tx Gigabit SMF Fiber SC to Copper RJ45 Ethernet Converter, UL Certified, up to 2km, 1310 nm TX		
10. 48V Passive <b>PoE Injector Adapter</b> PORT: 1× Gigabit PoE Port, 1× Gigabit Non-PoE Port SPEC: Data and Power Carried over The Same Cable At least 48V 18W Passive PoE Adapter		
11. 2 KM MINI FIGURE 8 (4 CORE Fiber Cable)		
12. Cat 6 Outdoor UTP Cable Pure Copper - 305 meters per roll  • Category 6 U/UTP Installation Cable, Outdoor, Gel Filled, Oxygen free copper (99.97% purity), Support PoE long-distance transmission, Black Customized MDPE outer sheath; meets ANSI/TIA 568-C.2 flame retardant class certified.		
13. S-Clamp Tension Holder		
14. CCTV Stainless Box 400MM*300MM*180MM 0.4mm Thickness		
15. Electrical Drop Cable #16		
16. Safety Circuit Breaker 15A		
Note to Piddows	Signature of Penresentative	

*Note to Bidders:* 

Signature of Representative	
Name of Representative	
Position	
Company	
Address	
Telephone/Fax/Email	

17. THHN #16 Electrical Wire	
18. 150 x 150 x 70mm Waterproof Box	
19. <b>Consumables</b> [screws, clamps, hose clamps, sea tapes (electrical, rubber), cable ties, guy wire, RJ45	
20. <b>Monitor 27"</b> with 99% sRGB & 1.07B colors at least 4K UHD (2560 x 1440) at 60 Hz   IPS with 350cd/m² brightness   3W integrated stereo speakers   Heigl (rotation), swivel, tilt   2 x HDMI, USB-C with DisplayPort 1.2 mode & Power Delivery up to 65W, Audio line-out	ht, pivot
21. <b>Desktop PC</b> Motherboard: At least Intel H610 Chipset Motherboard Proleast Intel Core i5-12400F Processor 18M Cache, up to 4.40 Cores 12Threads (Discrete Graphics Required) Graphics: At least 8GB RTX 4060 (At least DisplayPort x 3 HDMI x 1) System Memory: At least 16GB DDR4 3200M MemoryM.2 SSD Storage: At least 1TB M.2 NVME SSD Chassis: At least Mid Tower Form Factor (2 Front USB 3.0 Port) Power Supply: At least 750 Watts 80 Plus High Efficit PowerSupply. Operating System: Microsoft Windows 11 Professional. At least UPS AVR 650 Watts / 1.2Kva. At least the Keyboard & Mouse Bundle Mouse Pad	6. At least Hz System Drive 0, 1Type C iency
<ul> <li>22. Cleaning of the following existing cameras:</li> <li>BOSCH AUTODOME IP Dynamic 7000 HD with Metal Post - 5 units</li> <li>BOSCH DINION IP Bullet 5000 HD - 15 units</li> <li>BOSCH FLEXIDOME IP indoor 5000 HD- 44 units</li> </ul>	
23. Supply, Installation, configuration, and testing Video Management  System (VMS) -both existing and new cameras should be integrated Video Management System	
Note to Bidders:	Signature of Representative

Signature of Representative	
Name of Representative	
Position	
Company	
Address	
Telephone/Fax/Email	

24. Installation, termination, activation, configuration, supervision, and documentation.		
25. Knowledge Transfer and Training		
In compliance with Penublic Act No. 0104. Section 19, and the 2016 Pavised Implementing Pulse		

In compliance with Republic Act No. 9184, Section 18, and the 2016 Revised Implementing Rules and Regulations, Section 18, brand names are used because of compatibility with existing platforms or equipment which will maintain performance, functionality and useful life.

Note to Bidders:

Signature of Representative	
Name of Representative	
Position	
Company	
Address	
Telephone/Fax/Email	